

Product Specifications

PROGEF[®] PP Metric Piping System Specification

1. Scope

This specification covers requirements for the +GF+ Georg Fischer (later named only +GF+) **PP** Piping System, branded as **PROGEF[®] System**, intended for a wide range of applications including water, wastewater and effluent treatment as well as a wide range of chemical applications. The components of the PP pipe system are in accordance with the following standards.

2. Extract of the Material Specification of the PROGEF[®] System in β -PP-H

All PP pipes, fittings and valves from +GF+ shall be manufactured from Isotactic Polypropylene Homopolymeride **β -PP-H** or from Polypropylene random co-polymeride **PP-R** with a value of MRS 10 MPa, of which pipes and fittings are designed for 25 years of operation with an optimal chemical resistance. The material shall be designed for use with pressure bearing piping systems with long-term hydrostatic properties in accordance with EN ISO 15494, as supplied by +GF+.

Extract of Material characteristics of β -PP-H (Standard Values)

Characteristics	Value	Units	Test Standards
Density	0.90	g/cm ³	ISO 1183
Charpy notched impact strength at 23 °C	85	kJ/m ²	EN ISO 179/1eA
Charpy notched impact strength at 0 °C	4.8	kJ/m ²	EN ISO 179/1eA
Final inner surface roughness	< 1 μ m r_a -value		
Chemical resistance	DIBT agreement		based on the Medium list 40.1.4
Thermal expansion coefficient	0.16-0.18	mm/mK	DIN 53752
Temperature range	0 - 80 in °C *		
Operating pressure range for Pipes, Fittings and Ball Valve with \leq O.D. 110 mm:	10	bars at 20 °C	
Colour	7032	- RAL	

* Temperature raise up to 95 °C for short term (less than 30 min.) with low pressure (below 2 bars) is possible, if the system has been polyfused with the IR Plus Welding machine from +GF+

Product Specifications

Extract of Material characteristics of PP-R (Standard Values)

Characteristics	Value	Units	Test Standards
Density	0.91	g/cm ³	ISO 1183
Charpy notched impact strength at 23 °C	30.9	kJ/m ²	EN ISO 179/1eA
Charpy notched impact strength at 0 °C	3.4	kJ/m ²	EN ISO 179/1eA
Final inner surface roughness	< 1 µm r _a -value		
Chemical resistance	DIBT agreement	based on the Medium list 40.1.4	
Thermal expansion coefficient	0.16-0.18	mm/mK	DIN 53752
Temperature range	0 - 80 in °C *		
Operating pressure range for Pipes, Fittings and Ball Valve with ≤ O.D. 110 mm:	10	bars at 20 °C	
Colour	7032	- RAL	

For more detailed physical properties please see +GF+ literature reference GMST 5957/4 (planning fundamentals / July 2006), pages 34 and following.

3. Pipes

PROGEF® PP Pipes are made of **β-PP-H** and comply with a MRS class of 10. Processing of pipes is done according to EN ISO 15494 and DIN 8077 (dimensions) and DIN 8078 (quality specifications).

Pipes are approved by the DIBT1) (Nr. Z-40.23-4) and follow the confined quality specifications of the DIN Certco ZP2)-guideline A.9.4.1; chemical resistance complies with the DIBT-media list as a minimum. Processed pipes are straight and show a very low out of roundness. The wall structure is homogeneous, fine and shows no voids or inclusions.

Pipes show an excellent inner surface (ra < 1 µm for OD ≤ 110 mm). Pipes are fabricated in a stress relieving process. For OD ≤ 160 mm the OD-tolerances are strongly confined ("half the tolerance") compared to DIN 8077 to enable also an easy and straight forward socket welding process.

Impact resistance of pipe is equal or better compared to any PP-R material at temperatures below T = 20 °C. Pipe material has been designed for industrial service and an enhanced chemical resistance (esp. at elevated temperatures) based on modified thermo-stabilizer package used.

4. Fittings

All **PROGEF® PP** fittings shall be either as butt fusion type, metric sizes d 20 – d 400 mm, or socket fusion type, metric sizes d 20 – 110 mm, manufactured by +GF. The dimension of both fitting types fulfils the tolerance requirements of the standard EN ISO 15494. They need to be tested according to EN 10204. All threaded

Product Specifications

connections shall have pipe threads in accordance with the requirements of ISO 7-1. All butt fusion spigot fittings of the dimension d 20 – 225 mm shall be manufactured with laying lengths designed for use with the fusion machine IR-63 Plus and IR-225 Plus from +GF+.

4.1 Fitting Accessories

Backing flange metric sizes DN 15-315 mm shall be designed according to EN ISO 15494-1, in a thermo plastic-oriented design, consisting of 100% glass fibre reinforced polypropylene, PP-GF30, graphite black and UV stabilized. These flanges are manufactured in a seamless technology injection moulding process by +GF+. The flange shall be optimised with a V-groove in the inner diameter to ensure an evenly distributed force on the thermo plastic flange adapter. Connecting dimensions metric according to ISO 7005, EN 1092, DIN 2501; Bolt Circle Diameter PN 10; Inch: ANSI B 16.5, BS 1560; class 150

5. Valves

All **PROGEF**[®] valves shall be metric sizes manufactured by +GF+ or equal in accordance with EN ISO 16135 and following and ISO 8242, tested according to the same standard. All butt fusion valves shall also be manufactured with laying lengths designed for use with the fusion machine IR-63 Plus and IR-225 Plus from +GF+.

5.1. Ball Valves

All **PROGEF**[®] ball valves with metric sizes DN 15 - 100 mm in metric, shall be +GF+ Type 546 with true double union design manufactured by +GF+ in accordance with EN ISO 16135. Incorporated into its design shall be a safety stem with a pre-determined breaking point above the bottom O-ring, preventing any media leaking in the event of damage. The valve nut threads shall be buttress type to allow fast and safe radial mounting and dismounting of the valve during installation or maintenance work. Seats shall be PTFE with backing rings creating self-adjusting seals and constant operating torque. Backing rings and seals shall be EPDM or FPM. The handle shall include in its design an integrated tool for removal of the union bush. Union bush shall have fine-pitched left-hand threads to prevent possible unscrewing when threaded end connectors are removed from pipe. Following accessories shall be available:

- A Multi-Functional Model (MFM) in PPGF equipped with internal limit switches for reliable electrical position feedback, is mounted directly between the valve body and the valve handle. This MFM is also the necessary interface for later mounting of actuators.
- Mounting plate in PPGF with integrated inserts for later screw mounting on any support
- Lockable multi-functional handle

5.1.1. Electrically actuated ball valves

Electric actuators shall be Types EA11 (sizes DN 10-50 mm), EA21 (sizes DN 10-50 mm), EA31 (sizes DN 65-100 mm) shall be available manufactured by +GF+ in accordance with EN 61010-1, EC directives 89/336/EWG-EMV and 73/23/EWG, LKD and needs to be **CE** marked. Actuator housing shall be made

Product Specifications

of PPGF (polypropylene glass fibre reinforced), flame retardant with external stainless steel screws. All electric actuators shall have an integrated emergency manual override and integrated optical position indication. All electric actuator types (with the exception of EA11) shall have the following accessories available:

- Fail-safe unit
- Heating element
- Cycle extension, cycle time monitoring, and cycle counting
- Motor current monitoring
- Position signalisation
- Positioner Type PE25
- Limit switch kits Ag-Ni, Au, NPN, PNP
- AS Interface Control Box

Electric actuator specifications of the actuators shall be as follows:

Specification	EA11	EA21	EA31	EA42
Nominal torque (Nm)	10	10	60	100
Control time (s/90°)*	5	5	15	25
Cycles at 20°C *	150,000	250,000	100,000	75,000
Duty cycle ED at 25°C	40%	100%	50%	35%
Protection class	IP65 per EN 60529 - IP67 (for vertical cable mounting and wall feed through).			
Voltage	100-230, 50-60 Hz or 24V=/24V, 50/60 Hz versions			

* = at nominal torque

5.1.2. Pneumatically actuated ball valves

Pneumatic actuators shall be +GF+ Types PA11 (for valve sizes DN 15-25 mm) and PA21 (for valve sizes DN 32-50 mm) shall be available manufactured by +GF+. Pneumatic actuators shall be available as fail safe close, fail safe open and double acting and have an integrated optical position indication. Actuator housing shall be made of Polypropylene fibre glass reinforced (PPGF) and flame retardant. Actuators shall contain a preloaded spring assembly to ensure safe actuator operation and maintenance. Actuators shall contain integrated Namur interface for the easy mounting of positioners, limit switches and accessories. The Valve shall be equipped with a Multi-functional-module for reliable electric feedback, mounted directly between the valve body and the actuator as manufactured by +GF+.

For valve size DN 65 mm pneumatic actuators shall be Type PA 30 (fail safe to close or open function), Type P35 (double acting function).

For valve size DN 80 mm pneumatic actuators shall be Type PA 35 (fail safe to close or open function), Type P40 (double acting function).

For valve size DN 100 mm pneumatic actuators shall be Type PA 45 (fail safe to close or open function), Type 45 (double acting function)

Product Specifications

All actuators shall be manufactured by +GF+. Pneumatic actuators shall have an integrated optical position indication. Actuator housing shall be made of hard anodized aluminium. Actuators shall contain integrated Namur interface for the easy mounting of positioners, limit switches and accessories.

All pneumatically actuated ball valves shall have the following accessories available:

- Pilot valve remote or direct mounted in voltages 24VDC/AC, 110VAC, 240VAC
- Positioner Type DSR 201
- Limit switch kits Ag-Ni, Au, NPN, PNP
- Stroke limiter
- Manual override for all sizes up to d 110 mm
- AS Interface Control Bow with incorporated position feedback and a solenoid pilot valve

5.2. Diaphragm Valves

All **PROGEF**[®] diaphragm valves, metric sized, shall be either:

- Type 314 (true double union design, DN 15-50), or
- Type 315 (spigot design, DN 15-50) or
- Type 317 (flanged design, DN 15-150), or
- Type 319 T-valve as fully injected body and maximum dead leg of DN 2 (with butt fusion spigots, DN 15-100)

All diaphragm valve shall be manufactured by +GF+ in accordance with EN ISO 16138. The Upper body shall be PPGF (polypropylene glass fibre reinforced) connected to the lower body with exposed stainless steel bolts. A position indicator integrated into the hand wheel must be present to determine diaphragm position. Diaphragms are to be EPDM, FPM, NBR, CSM, or PTFE with EPDM or FPM supporting diaphragm. Following Option shall be available:

- Handwheel with build-in locking mechanism

5.2.1. Pneumatically actuated diaphragm valves

Pneumatic diaphragm actuators shall be +GF+ Type DIASTAR sizes DN 15-150 mm. Pneumatic actuators shall be available as fail safe close, fail safe open and double acting and have an integrated optical position indication. Actuator housing shall be made of PPGF (polypropylene glass fibre reinforced), flame retardant and NEMA 4X or IP 65 corrosion resistance. Actuators shall contain a preloaded galvanised steel spring assembly to ensure safe actuator operation and maintenance. All pneumatically actuated diaphragm valves shall have the following accessories available:

- Pilot valve remote or direct mounted in voltages 24VDC/AC, 110VAC, 240VAC
- Positioner Type DSR 100/101

Product Specifications

- Limit switch kits Ag-Ni, Au, NPN, PNP
- Stroke limiter & emergency manual override
- AS Interface Control Box with incorporated position feedback and solenoid valves

5.3. Butterfly Valves

All **PROGEF**[®] butterfly valves, metric sizes DN 50 (1 1/2") – 200 (8") mm, shall be +GF+ Type 567 wafer type with a double eccentric disc design manufactured by +GF+ in accordance with EN ISO 16136. Seals shall be available in both EPDM and FPM. The lever handle shall be lockable in increments of 5 degrees. There shall always be six teeth engaged between the ratchet and the index plate to ensure accurate and safe positioning of the lever. There shall be the option of fine adjustment by use of a specific hand lever, allowing the disc to be opened at any angle between 0° und 90°. As an option, the hand lever shall be lockable. The hand lever shall be manufactured of high strength PPGF (polypropylene glass fibre reinforced). The option of an integrated electric position indicator shall be available. The electric position indicator shall be integrated into the mounting flange. Butterfly valves shall have low actuation torque to enable easy operation.

All **PROGEF**[®] **Plus** butterfly valves, metric sizes DN 250-300, shall be +GF+ Type 367, design manufactured by +GF+ in accordance with EN ISO 16136.

5.3.1. Electrically actuated butterfly valves

Electric actuators shall be +GF+ Types EA31 or EA 42 depending on valve size shall be manufactured by +GF+ in accordance with EN 61010-1, as per the above specifications. Actuator housing shall be made of PPGF (polypropylene glass fibre reinforced), flame retardant and external stainless steel screws. All electric actuators shall have an integrated emergency manual override and integrated optical position indication. All electric actuator types shall have the following accessories available:

- Fail-safe unit
- Heating element
- Cycle extension, cycle time monitoring, and cycle counting
- Motor current monitoring
- Position signalisation
- Positioner Type PE25
- Limit switch kits Ag-Ni, Au, NPN, PNP
- AS Interface Control Box

5.3.2. Pneumatically actuated butterfly valves

Pneumatic actuators shall be +GF+ Types PA 35 (metric sizes DN 50-65 mm), PA40 (metric size DN 80 mm only), PA45 (metric size DN 100 -125), PA55 (metric size DN 150-200 mm) shall supplied by +GF+. Pneumatic actuators

Product Specifications

shall be available as fail safe close, fail safe open and double acting and have an integrated optical position indication. Actuator housing shall be made of hard anodized aluminium. Actuators shall contain integrated Namur interface for the easy mounting of positioners, limit switches and accessories. All pneumatically actuated butterfly valves shall have the following accessories available:

- Pilot valve remote or direct mounted in voltages 24VDC/AC, 110VAC, 240VAC
- Positioner Type DSR 201
- Limit switch kits Ag-Ni, Au, NPN, PNP
- Stroke limiter
- AS Interface Control Bow with incorporated position feedback and a solenoid pilot valve

5.4. Check Valves

All PROGEF[®] Ball check valves, according to EN ISO 16137, metric sizes DN 15-50 mm shall be +GF+ Type 360 true double union design. Seals shall be EPDM or FPM. Union bush shall have a left hand thread to prevent possible unscrewing when threaded end connectors are removed from pipe. This valve shall be suitable for mounting in a vertical position.

5.5. Wafer Check Valves

All PROGEF[®] Wafer Check Valves shall be +GF+ Type 369, metric size DN 32-300 mm shall be supplied by +GF+ offering a minimum water column of 2 m for sealing. They have to be equipped with a spring (either in 316 stainless steel or Hasteloy C) guaranteeing closing in all installation positions. Attention: A stabilizing pipe zone of at least 5 times nominal diameter (DN) before and after the wafer check valve should be provided.

5.6. Pressure regulating valves

All **PROGEF[®]** pressure regulating valves as supplied by +GF+ shall have the following characteristics:

Pressure ranges for all pressure regulating valves are the following:

DN 10 – 50	from 0 up to max 10 bar
DN 65-80	from 0 up to max 6 bars
DN 100 –	from 0 up to max. 4 bars

5.6.1. The Pressure Reducing Valve

as supplied by +GF+ reduces the pressure within the system to a pre-set value. By using the differential pressure, the pressure reducing valve adjusts

Product Specifications

itself to the set working pressure. The outlet pressure (working pressure) is not directly related to the inlet pressure. If the outlet pressure increases or decreases above/below the desired value, the diaphragm is lifted against the spring force or pressed down by the spring force, as the case may be, by the outlet pressure. The pressure reducing valve begins to close/open until a state of equilibrium is re-established; in other words, the outlet pressure remains constant irrespective of an increasing or decreasing inlet pressure. Following types and sizes are available:

- Type V82, compact Pressure Reducing Valve with an integrated manometer, sizes DN 10 -100 mm
- Type V182, compact Pressure Reducing Valve offering easy adjustment and real time visual control of the actual pressure reduction on the integrated manometer, sizes DN 10-40 mm
- Type V782, compact Pressure Reducing Valve, offering an easy adjustment, excellent flow rate and very low hysteresis, sizes DN 10-40 mm

5.6.2. Pressure Relief Valve

as supplied by +GF+ serves to keep the working or system pressures constant, to balance out pressure pulsation, and to reduce pressure peaks in process systems. The third pipe spigot fitted on the valve body means the valve can be installed directly in the main pipeline. If the inlet pressure rises above the set value, the pressurized valve piston is lifted against the spring force. Consequently, the valve opens and there is a reduction of pressure in the outlet pipe. The excess pressure can exhaust or be redirected via the third outlet. The valve closes as soon as the inlet pressure sinks below the pre-set spring tension. Following types and sizes are available:

- Type V185, Pressure Relief Valve, sizes DN 10-50 mm
- Type V85, Pressure Relief Valve, sizes DN 65 -100 mm

5.6.3. The Pressure Retaining Valve

as supplied by +GF+ serves to keep the working or system related pressures constant, to balance out pressure pulsation, and to reduce pressure peaks in chemical process systems. If the inlet pressure rises above the set value, the pressurized valve piston is lifted against the spring force. Consequently, the valve opens and there is a reduction of pressure through the outlet pipe. The valve closes as soon as the inlet pressure sinks below the pre-set spring tension. Following types and sizes are available:

- Type V186, Pressure Retaining Valve, sizes DN 10-50 mm
- Type V86, Pressure Retaining Valve, sizes DN 65-100 mm
- Type V786, Pressure Retaining Valve, sizes DN 10-40 mm

Product Specifications

6. Instrumentation

The following parameters can be measured (Sensors), indicated and/ or transmitted (Transmitters) to PLC, PC and other Data Acquisition Systems. All products comply with the CE standard

Parameter	Technology	Compatible liquids (*)
Flow	Paddlewheel	Clean liquids
	Vortex	Ultra pure liquids
	Magmeter	Contaminated liquids
Level	Hydrostatic	All liquids
pH-ORP	Glas electrodes	All liquids
Conductivity	Contact	All liquids
Pressure	Piezoresistive	All liquids
Temperature	Pt1000	All liquids

(*) Please check first the sensors limitations (Data sheet) and chemical resistance list

6.1 Sensors

The sensors listed here after will transfer the measured value to a +GF+ Transmitter, allowing simple calibration and maintenance of the devices. Alternatively the measured values of the sensors could be send directly to a PLC, PC or other local made electronics using either an analogue signal (mA, open collector or sinusoidal voltage) or a digital signal called S3L (+GF+ Signet serial signal).

Depending on the sensors type, special installation fittings shall be used to connect it into the pipeline: Installation T-Fitting (DN15-50 mm) with double true union in **PROGEF PP-H** with as supplied by +GF+. Following connection shall be available: Weld-o-let, direct union 1/2", 3/4 " ISO, 3/4" NPT, Submersion kits. These fittings shall be offered in version IR Plus butt fusion.

6.1.2 Flow sensors

6.1.2.1 Paddlewheel sensors

515 and 525 sensors:

All the sensor of this family are considered as a "sinusoidal" sensor. This sensor from +GF+ SIGNET requires no external power source to produce a signal. Internal to the body of the sensor is a wire coil which when excite by the rotor assembly produces a small sinusoidal signal. The rotor assembly consists of four paddles; inserted into each of the paddles of the rotor are magnets. As liquid flows past the rotor assembly it rotates, as each of the four paddles pass the center of the body a sine wave signal is produced (two paddles of the rotor produces a full AC sine wave). The sensors as manufactured by +GF+ SIGNET produce a signal output which is proportional to the flow rate. A K-factor (number of pulses generated by the sensor per 1 liter or 1 gallon

Product Specifications

of fluid that passes the sensor) is used to define the size of the pipe that the sensor is inserted into.

3-2536 and 3-2537 sensors:

All sensors of this family of sensors are considered as a “Hall Effect” sensor. Internal to the +GF+ SIGNET sensors body is an open collector relay. The sensor is supplied with a voltage from the 3-8550 transmitters or an external power supply ranging from 5 to 24 volts. This voltage is switched through the open collector relay as the paddlewheel (rotor) of the sensor rotates.

The sensor’s rotor assembly has four paddles. Inserted in to each of the paddles is a magnet. As the paddles pass the center of the sensors body, the magnetic field switches the open collector relay on and off which generates a square wave pulse as manufactured by +GF+ SIGNET. A pulse is a complete cycle of on and off of the open collector relay.

The sensors pulse output is directly proportional to the fluids velocity. A K-factor (number of pulses generated by the sensor per 1 liter or 1 gallon of fluid that passes the sensor) is used to define the size of the pipe that the sensor is inserted into.

6.1.2.2 Vortex sensors:

Located inside the body of the +GF+ SIGNET Type 7000 and 7001 Vortex sensor is a “Bluff Body and a Piezoelectric sensor. As fluids passed the bluff body, the fluid creates small swirls called Vortices. As the vortices pass the piezoelectric sensor, the sensor vibrates. As the flow velocity increases the vibration on the surfaces of the piezoelectric sensor increases. This vibration or movement of the piezoelectric sensor is translated into electrical signals. The electrical signals are then conditioned and translated into pulse signal (K-factor), which will be send to a +GF+ SIGNET Transmitter unit.

6.1.2.3 Magmeter

The Magmeter sensor of +GF+ SIGNET consists of two metallic pins that produce a small magnetic field across the inside of the pipe. The Magmeter measure the velocity of a conductive liquid (20 μ S or greater) as it moves across the magnetic field produced by the Magmeter. The magnetic field produced by the sensor is directly proportionally to the flow rate of the fluid. The magnetic signal is conditioned and translated in to a pulse signal (K-factor). The Magmeter of +GF+ SIGNET is offered as a blind output (frequency or 4-20 mA), or with a integral display and control relays.

6.1.3 Level sensor (hydrostatic level)

Hydrostatic pressure is the pressure exerted on a column of fluid by the weight of the fluid above it. Internal to the +GF+ SINGET PVDF sensor body is a ceramic diaphragm sensor and capillary tube/cable assembly. The ceramic diaphragm sensor exposed to the fluid senses the hydrostatic pressure of the fluid and compares the pressure to the atmosphere pressure that is sensed by the capillary tube/cable assembly. Because the hydrostatic level sensor from +GF+ SIGNET only senses the pressure of the fluid, interference and inaccuracies of the signal are dramatically

Product Specifications

reduced. The measured signals are then conditioned send to a +GF+ SIGNET Transmitter unit.

6.1.4 pH sensors

All pH sensors from +GF+ SIGNET are constructed of three key elements, measuring cell, reference cell and the reference junction. The measuring cell is constructed of hydrogen sensitive glass that can detect the concentration of hydrogen ions (+H) in a solution. The concentration of +H ions directly determines the pH of the fluid. The reference cell is used to provide a stable reference mV-signal that the measuring cell compares its signal to. The reference junction allows the reference cell to come in contact with the fluid being measured. The measured signal are then conditioned and send to a +GF+ SIGNET Transmitter unit.

6.1.5 ORP sensors

All ORP sensors from +GF+ SIGNET are constructed similar to the pH sensor with one exception. The hydrogen sensitive glass is replaced with a noble metal such as platinum or gold.

The noble metal measures the activity of oxidizing or reducing chemicals agents. The electrical signals are then conditioned and translated into pulse signal (K-factor), which will be send to a +GF+ SIGNET Transmitter unit.

6.1.6 Conductivity sensors

All Conductivity sensors from +GF+ SIGNET are manufactured using two electrodes made of stainless steel (other material available if there is a chemical compatibility issue). Conductivity sensors measure the ability of a fluid to conduct an electrical current between the two electrodes. The conductivity monitor/transmitter sends a signal into one the electrode and depending on the fluids availability to conduct a charge (concentration of ions) measures the amount of current required to sense the signal on the second electrode. Other important fact to consider, select a sensor that has the proper cell constant (depends on the conductivity level). All conductivity sensors from +GF+ SIGNET have a temperature compensation circuits in order to increase the sensors accuracy.

6.2 Transmitters

The analogue data transfer with or without display as well as optional relays contacts will be provided by a +GF+ Transmitter. This transmitter can be built:

- Directly inline on the sensor (INTEGRAL Version)
- On a wall, pipe, frame etc... by using a universal mounting kit (UNIVERSAL Version)
- On the door of a cabinet or a panel (PANEL Version)

The analogue or digital display version will allow to set up all process parameters like the measuring range, relay set points and to calibrate the piping system.

A Multi parameter (Multi channel) version in panel version allows to build his own customised transmitter by mixing and matching In- and Output as supplied by +GF+.

Product Specifications

Following selection are possible:

- 2,4 or 6 sensor input (Flow, Level, pH-ORP, Conductivity, Pressure Temperature)
- 0,2 or 4 analogue output (4-20 mA or 0-10 Volts)
- 0,2,4,6 or 8 relay output
- Power supply 12-30 VDC or 110-230 VAC

6.3 Batch control

A Batch controller manufactured by +GF Signet Type 5600 allow dosing a pre-selected quantity of liquid. After a start signal (local or remote), the 5600 will close a contact to open an automatic valve and/or switch on a pump, count up pulses coming from a flow sensor (Paddlewheel, Vortex or Magmeter) and open the contact again as soon as the pre-selected quantity is reached. This batch process is repeatable and the +GF+ Batch Transmitter is designed for intensive industrial applications.

7. Piping System Pressure Rating

All components are designed for a maximal operating pressure of 10 bars at 20 °C up to an external dimension of DN 200 mm. Binding is continuously updated product information available on our homepage.

8. Marking

All components are embossed with a permanent identification during the production process to ensure full traceability. The following information will be mentioned:

- Production lot number
- Material
- Dimension
- Pressure rating

9. Welding and assembly

All butt fusion fittings and valves shall also be manufactured with laying lengths designed for use with fusion machine IR-63 Plus, IR-225 Plus and IR-315 Plus from +GF+, allowing welds with increased mechanical and chemical stability than conventional welding methods(socket- and butt fusion). The IR Plus fusion technology uses the material temperature of the welding zone to determine the end of the fusion process. As soon as the welding zone temperature of the fitting is below the defined unclamping temperature, the fusion process (cooling time) is being finished. The cooling time for the IR-Plus fusion machines is calculated on the basis of the ambient temperature and the bead surface temperature. To increase the cooling capacity, an additional ventilation is included in the IR-225 Plus. Only authorised welder by +GF+ are allowed to perform fusion on the IR Plus machines.

The welding and the installation should be in accordance with +GF+ Piping Systems Guide to the Installation and Use of Plastic Pipeline. For further information and training regarding the fusion technique and machine IR Plus please contact Georg Fischer support under +41 52 631 11 11 or e-mail to info.ps@georgfischer.com.

Product Specifications

10. Pipe Support System

Pipe Support System shall be KLIP-IT, sizes d10-400, manufactured by +GF+.

11. Quality

Pipes, fittings, solvent cement, cleaner, valves and accessories shall be manufactured in an environment operating a Quality Assurance System to ISO 9001 and a Environmental Management System conform to ISO 14001.

12. Uniformity

Pipes, fittings, valves, cleaner and Fusion IR Plus machines shall be supplied from one manufacturer, namely +GF+, to ensure correct and proper jointing between components and uniform chemical and physical properties of the piping system.

13. Training, Certification and Installation

Site personnel, involved with **PROGEF**[®] piping installation, shall undergo training and certification from an authorised +GF+ representative prior to performing any jointing operations on site. Installation, including support spacing and expansion considerations, shall be in accordance with the +GF+ written recommendations.