

Engineered specifically for small pipe diameter applications, the Signet 2100 Turbine Flow Sensor provides accurate readings in two flow ranges: 0.3 to 3.8 lpm and 3 to 38 lpm (0.1 to 1 gpm and 0.8 to 10 gpm).

The injection-molded PVDF body and ceramic bearings provide excellent chemical compatibility and long service in dosing and batching applications. Union piping and tubing connections along with removable NEMA 4X electronics allow for easy assembly and field replaceability. The 2100 can be used with DN8 (1/4 in.), DN10 (3/8 in.), DN15 (1/2 in.) tubing, or DN15 (1/2 in.) piping for simple installation. End connections are available in PVDF for hose barbs, fusion socket or IR/butt fusion, and in PVC for socket or NPT thread.

Features

- Operating range of 0.38 to 38 lpm (0.10 to 10 U.S. gpm)
- Non-magnetic turbine
- Union ends for various connector types
- End connector kits for rigid or flexible tubing or DN15 (1/2 in.) pipe
- PVDF & ceramic wetted parts provide superior chemical compatibility
- For use with both clear and opaque fluids
- Small and compact design
- 4.6 m (15 ft) cable
- Features removable electronics that installs from either side of the sensor
- Sensor mounts at any angle



Applications

- Chemical Addition
- Textile Dyeing
- High-purity Chemical Dispensing
- Water Addition
- Fertigation
- Dosing
- Pump Protection
- Not suitable for gases

Specifications



General		
Operating Range	-L = 0.38 to 3.8 lpm	(0.10 to 1 U.S. gpm)
Pipe Size Range	-H = 3 to 38 lpm	(0.8 to 10 U.S. gpm)
Linearity	±3% of reading	
Repeatability	±0.5% of reading	
Pipe Size Range	DN15 (½ in.)	
Hose size	DN8 (¼ in.), DN10 (⅜ in.), DN15 (½ in.)	
Wetted Materials		
Sensor Body/Rotor	PVDF	
Shaft/Bearings	Ceramic	
O-rings	-1 = FPM, -2 = EPR (EPDM)	
Electronics Housing	PBT (polybutylene terephthalate)	
	EVA (ethylene vinyl acetate)	
Electrical		
Power	5 to 24 VDC ±10%, regulated, 1.5 mA max.	
	Reverse polarity protected	
Output	Open collector, sinking, max 30 mA	
Cable Length	4.6 m (15 ft) can be extended up to 300 m (1000 ft)	
Cable Type	PVC jacketed, 2 conductor twisted pair with shield (22 AWG)	
Max. Temperature/Pressure Rating		
	16 bar @ 20 °C	232 psi @ 68 °F
	9.3 bar @ 70 °C	130 psi @ 158 °F
Operating Temperature	-20 °C to 70 °C	-4 °F to 158 °F
Storage Temperature	-15 °C to 80 °C	5 °F to 176 °F
Shipping Weight		
	0.15 kg	0.33 lb
Standards and Approvals		
	CE	
	RoHS compliant	
	China RoHS	
	Manufactured under ISO 9001 for Quality and ISO 14001 for Environmental Management	

See Temperature and Pressure graphs for more information.






Dimensions

L = overall length

All sockets	102 mm	4 in.
Butt fusion/IR	170 mm	6.7 in.
¼ in. Barb	124 mm	4.9 in.
⅜ in. Barb	127 mm	5 in.
½ in. Barb	132 mm	5.2 in.



System Overview

Panel Mount	Field Mount - Pipe, Tank, Wall
Signet Instruments 5075 5500 5600 8550 8900 9900	Signet Instruments 8550 9900 with 3-8050 Universal Mount Kit
	
Signet 2100 Flow Sensor 	
End Connector options Fusion, threaded or solvent socket connectors for DN15 (1/2 in.) pipe	Hose barb connectors for DN8, DN10, or DN15 (1/4 in., 3/8 in. or 1/2 in.) flexible tubing
	
All sold separately	


Application Tips

- All socket and hose barb connector kits are sold individually.
Two kits are required for each sensor.
- Mount at any angle.
- Junction block, 3-8050-1 recommended if standard cable is extended to maximum 300 m (1000 ft)


Operating Temperature/Pressure Graphs

Note:


The pressure/temperature graphs are specifically for the Signet sensor. During system design the specifications of all components must be considered. In the case of a metal piping system, a plastic sensor will reduce the system specification. When using a PVDF sensor in a PVC piping system, the fitting will reduce the system specification.



Low Flow




High Flow



Please refer to Wiring, Installation, and Accessories sections for more information.

Ordering Information



Mfr. Part No.	Code	O-ring Material	Flow Range
Turbine flow sensor, PVDF body and rotor, for use with various end-connectors			
3-2100-1L	159 000 001	FPM	low, 0.38 to 3.8 lpm (0.10 to 1 gpm)
3-2100-2L	159 000 003	EPR (EPDM)	low, 0.38 to 3.8 lpm (0.10 to 1 gpm)
3-2100-1H	159 000 002	FPM	high, 3 to 38 lpm (0.8 to 10 gpm)
3-2100-2H	159 000 004	EPR (EPDM)	high, 3 to 38 lpm (0.8 to 10 gpm)

*Note: To install this flow sensor, end fittings must be installed on both ends of the sensor.
See selection below

Mfr. Part No.	Code	Type of End Fitting
End fitting for Model 2100 sensor		
3-2100-31	159 000 005	Hose barb connector kit, PVDF, 1/2 inch (1-hose barb and 1-ring nut)
3-2100-32	159 000 006	Hose barb connector kit, PVDF, 3/8 inch (1-hose barb and 1-ring nut)
3-2100-33	159 000 007	Hose barb connector kit, PVDF, 1/4 inch (1-hose barb and 1-ring nut)
3-2100-34	159 000 008	Fusion socket connector, PVDF, DN15 1/2 inch (1-fusion socket and 1 ring nut)
3-2100-35	159 000 009	Butt Fusion/IR connector kit, PVDF, DN15 1/2 inch (1-IR socket and 1 ring nut)
3-2100-36	159 000 010	Metric socket connector kit, PVC, 1/2 inch (1-solvent socket and 1 ring nut)
3-2100-37	159 000 011	SCH 80 socket connector kit, PVC, 1/2 inch (1-solvent socket and 1 ring nut)
3-2100-38	159 000 012	NPT thread socket connector kit, PVC, 1/2 inch (1-threaded socket and 1 ring nut)

Accessories and Replacement Parts

Mfr. Part No.	Code	Description
1220-0018	159 000 019	O-rings FPM (2 required per sensor)
1224-0018	159 000 020	O-rings EPR (EPDM) (2 required per sensor)
3-2100.390-1L	159 000 015	Turbine Lo Flow with FPM O-rings (replacement body)
3-2100.390-1H	159 000 016	Turbine Hi Flow with FPM O-rings (replacement body)
3-2100.390-2L	159 000 017	Turbine Lo Flow with EPR (EPDM) O-rings (replacement body)
3-2100.390-2H	159 000 018	Turbine Hi Flow with EPR (EPDM) O-rings (replacement body)
3-2100.390	159 000 014	Electronics Module with 4.6 m (15 ft) cable
3-8050-1	159 000 753	Universal junction box

3-2100.099 Rev B (10/11)

© Georg Fischer Signet LLC

3401 Aerojet Avenue, El Monte, CA 91731-2882 U.S.A. • Tel. (626) 571-2770 • Fax (626) 573-2057 • www.gfsignet.com • e-mail: signet.ps@georgfischer.com
Specifications subject to change without notice. All rights reserved. All corporate names and trademarks stated herein are the property of their respective companies.