



Type 563
Aquatic /
Water Park
Butterfly Valve

+GF+

GEORG FISCHER
PIPING SYSTEMS

Type 563 Water Park / Aquatic Butterfly Valve

The 563 has been specially designed to fulfill aquatic / water park requirements. The table below shows the main differences between the 563 Water Park version and 567 Industrial Version.

Feature		563	567
Size Range	DN50-200	✓	✓
	DN250 – 300	end 2008	✓
Materials	PVC-U	✓	✓
	PVC-C		✓
	ABS		✓
	PP-H	✓	✓
	PVDF		✓
Actuation	Electric		✓
	Pneumatic FC / DA	✓	✓
	Pneumatic FO		✓
Seals dedicated for aquatic applications EPDM / FPM		✓	
Seals dedicated for Chemical / Industrial EPDM / FPM			✓
Special Versions	Silicone / Oil Free		✓
Bare shaft version			✓
Manual over-ride, Electric Feedback			✓
Pressure rating	Manual (External)	PN10	PN10
	Pneumatic (External)	PN4	PN10
	Manual (Internal)	PN4	PN10
	Pneumatic (Internal)	PN4	PN10
Packaging (minimum sales quantity) DN50-200		Double	Single
Approvals	Dibt, NSF, ACS, WRAS etc.		✓
Chemical / industrial applications			✓



Manual version



Pneumatic version



Minimum packing quantity
DN50-200, DN250-300 are single



Perfect for aquatic use



GEORG FISCHER
PIPING SYSTEMS